

Take on any task with the Z MasterRegistered 2000 zero-turn mower. Constructed for professional use with a 7 gauge steel TURBO FORCERRegistered cutting deck for fast, clean work. With the customizable MyRIDE Suspension System to isolate bumps and vibrations, you'll stay comfortable even on the longest days.

Anti Scalp Wheels	Standard
Blade Tip Speed	18,500 ft/min / 5,638 m/min
CARB Compliant	CARB Compliant
Caster Tires	13 in. x 6.5 in. - 6 in. (33 cm x 16.5 cm - 15.2 cm) Pneumatic
Clutch	Electromagnetic
Cutting Width	52 in. / 132 cm
Deck Design	5.5" (14 cm) deck depth, 7-Gauge High-Strength Steel TURBO FORCERRegistered w/ bull-nose bumper
Discharge Chute	Rubber
Drive Tires	Voodoo Trac 24 in. x 9.5 in. - 12 in. (61 x 24.1 - 30.5 cm)
Engine	Kawasaki FX730V
Engine Brand	Kawasaki
Engine Displacement (cc)	747 cc
Engine Horsepower	23.5 hp
Foot Operated Height of Cut	Standard
Forward Ground/Transport Speed	Up to 10.0 mph / 16.0 kph
Fuel Capacity	7 gal. / 26.5 L / 28 Qt.
Fuel Type	Gasoline
Height of Cut	1.5 - 5.0 in. / 3.8 - 12.7 cm in 0.25 in (0.64 cm) increments
Hitch Bracket	Standard
Hour Meter	Standard Hour Meter
Ignition	Electric
Lighting	LED Headlights
Notes:	Hitch: Integrated Receiver Hitch - 2 in. x 2 in. 80 lbs. (36.3 kg) max tongue, 250 lbs. (113.4 kg) max tow
Product Type	Zero Turn Mower
Product Use	Commercial
Roll-Over Protection (ROPS)	Folding; Standard
Spindle Housing	8 in / 20.3 cm Diameter Aluminum (Non Greasable) Ball Bearing, 1 in / 2.5 cm Shaft
Start Type	Electric
Steering Controls	1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened
Tool Mounting Capability	Side Console / Rear Guard Ready

Transmission

Hydro-Gear ZT-3400