

You work too hard to let your lawn dictate your leisure schedule. Get serious comfort and a beautiful cut with Toro's 42 in. TimeCutter. Combining a perfect blend of maneuverability and power, this mower makes quick work of the toughest tasks. And you'll enjoy luxury comfort when the ride gets rocky with the MyRIDER[®] suspension system that saves your body from the toughest terrain. This mower is easier to handle than ever with Toro's Smart Speed[®] Technology, which gives you total control over the mowing speed. And you can rest easy knowing that Toro stands behind its mowers with a 3-year, 300-hour commercial engine warranty.^{??} And as a Toro owner, you'll have access to more than 3,000 servicing dealers across the U.S. and Canada ready to assist you. Count on it.

Armrests	Standard
Blade Tip Speed	17,810 ft/min / 5,428 m/min
Box Dimensions	82 in. x 49 in. x 52 in. / 208.3 cm x 124.5 cm x 132.1m
CARB Compliant	Not CARB Compliant
Caster Tires	11 in. x 4 in. (27.9 cm x 10.2 cm)
Comfort Platform	MyRIDERegistered Suspension System
Controls	Dual Wrap Around Levers
Cup Holder	Included
Cutting Width	42 in. / 107 cm
Deck Design	42" IronForgedRegistered Fabricated Deck
Deck Material	10 Gauge Steel
Discharge Chute	Side
Drive Tires	18 in. x 7.5 in. (45.7 cm x 19 cm), 18" x 7.5" (45.7 cm x 19 cm)
Drive Type	Rear-Wheel Drive
Engine	Kohler 22 hp**
Engine Brand	Kohler
Engine Displacement (cc)	725 cc
Engine Horsepower	22.0 hp
Foot Operated Height of Cut	Optional
Forward Ground/Transport Speed	Up to 7.0 mph / 11.2 kph
Forward Mowing Speed	Up to 7.0 mph / 11.2 kph
Fuel Capacity	3 gal. / 11.4 L / 12 Qt.
Fuel Type	Gasoline
Height of Cut	1.5 - 4.5 in. / 3.8 - 11.4 cm
Hitch Bracket	Standard
Hour Meter	Optional
Included in the Box	1 Battery, Engine Oil
Number of Blades	2
Product Features	Cup Holder, Electric Start, Hitch Bracket, IronForged Deck, MyRIDE Suspension System, Smart Speed
Product Use	Residential
Recommended Oil Type	10W - 30 with filter change
Seat	18" Handcrafted High Back with Arm Rests - Lever Slide
Start Type	Electric
Steering Controls	Dual Wrap Around Levers
Steering Dampeners	Pro-Control Dampers
Terrain Type	Flat with Obstacles
Tires	11 in. x 4 in. (27.9 cm x 10.2 cm) Front, 18 in. x 7.5 in. (45.7 cm x 19 cm) Rear, 11" x 4" (27.9 cm x 10.2 cm) Front, 18" x 7.5" (45.7 cm x 19 cm) Rear
Tow Speed	Up to 4.0 mph / 6.4 kph
Transmission	Dual Hydrostatic HG-ZT2100
Trim Speed	Up to 5.5 mph / 8.8 kph
Washout Port	Standard
Yard Size	Up to 2 acres