## **Brooks Factory Direct Trailers - Oswego**

Phone: 3152072047 7911 State Route 104

Oswego, NY

Email: info@brookstrailers.com



# 30 in. (76 cm) Power Max HD 1030 OHAE 38830 Two-Stage Gas Snow Blower

Stock#: TO-00032	Year: 2023	Manufacturer: Toro				
URL: https://brooksfactorydirecttrailers.com/30-in-Jp6p.html						

Price Call For Pr	ice
-------------------	-----

## **Description**

### **Overview**

Old man winter will consider retiring when you roll out this Power Max HD 1030 OHAE 30in., 302cc 2-stage, 4-cycle snow-crushing machine. Send the snow flying 49 feet away while making a path 30 inches wide and 21 inches deep. This premium model comes with self-propelled triggerless steering for tight and easy turn---no triggers or levers required.

It's a one-handed wonder thanks to Quick Stick(r) control for rapid and effortless chute direction and chute deflector adjustment. Our Anti-Clogging, anti-slow-you-down, System meters snow intake to prevent clogging and maximize clearing efficiency, without shear pins. We brake (not break) for obstacles---if the hardened gears and commercial-grade auger hits hard material the engine will purposely stall to prevent damage. The hits keep coming with steel chute, 16" tires, hand warmers, LED light and a robust 3-year limited warranty. Tell Old Man Winter to get off your driveway

Choose the right fuel for your snow blower. For best starting results use Non-ethanol fuel with an octane rating of 87 or higher. Use fresh fuel less than 30 days old, add fuel stabilizer to reduce starting problems. Do not mix oil with gas.

#### **Specifications**

- Auger System Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial- Grade; no shear pins needed
- Chute Control Quick Stick(r) (200° Rotation), Steel, Double Deflector
- Clearing Width 30" (76.2 cm) clearing width, 21" (53.3 cm) intake height
- Engine Toro Premium 302cc OHV 4-cycle
- Engine Displacement 302cc
- Lighting LED Headlight Standard
- Starter Electric Start
- Throw Distance Up to 49' (14.9 m)\*
- Tires 16" (41 cm)